


SI...C,ET-2RS



滑动摩擦副：钢 / PTFE 复合材料($d \leq 30$)
钢 / PTFE 编织物 ($d \geq 15$)



SI...C

SI...ET-2RS

select	Inquiry	Bearing number	Dimension mm																load rating kN		Weight kg
			d	B	d _k	C ₁ max	d ₂	G 6H	h ₁	l ₃ min	l ₄	l ₅	l ₇	W	d ₃	d ₄	rs min	a°	dynamic load	static load	
SI5C	5	6	10	4.5	21	M5	30	11	40.5	5	11.5	10	10	13	0.3	13	3.6	8.1	0.021		
SI6C	6	6	10	4.5	21	M6	30	11	40.5	5	11.5	11	11	13	0.3	13	3.6	8.1	0.021		
SI8C	8	8	13	6.5	24	M8	36	15	48	5	13	13	13	16	0.3	15	5.8	12.9	0.039		
SI10C	10	9	16	7.5	29	M10	43	20	57.5	6.5	15	16	16	19	0.3	12	8.6	17.6	0.065		
SI12C	12	10	18	8.5	34	M12	50	23	67	7	18	18	19	22	0.3	10	11	24.5	0.096		
SI15C	15	12	22	10.5	40	M14	61	30	81	8	21	21	21	26	0.3	S	18	36	0.16		
SI15ET-2RS	15	12	22	10.5	40	M14	61	30	81	8	21	21	21	26	0.3	8	25	36	0.16		
SI17C	17	14	25	11.5	46	M16	67	34	90	10	24	27	25	29	0.3	10	22	45	0.24		
SI17ET-2RS	17	14	25	11.5	46	M16	67	34	90	10	24	27	25	29	0.3	10	32	45	0.24		
SI20C	20	16	29	13.5	53	M20x1.5	77	40	103.5	10	25.5	30	28	34	0.3	9	31	60	0.35		
SI20ET-2RS	20	16	29	13.5	53	M20×1.5	77	40	103.5	10	25.5	30	28	34	0.3	9	45	60	0.35		
SI25C	25	20	35.5	18	64	M24x2	94	48	126	12	33	36	35	42	0.6	7	51	83	0.66		
SI25ET-2RS	25	20	35.5	18	64	M24×2	94	48	126	12	33	36	35	42	0.6	7	85	83	0.66		
SI30C	30	22	40.7	20	73	M30x2	110	56	146.5	15	37.5	46	42	50	0.6	6	65	110	0.98		
SI30ET-2RS	30	22	40.7	20	73	M30×1.5	110	56	146.5	15	37.5	46	42	50	0.6	6	110	110	0.98		
SI35ET-2RS	35	25	47	22	82	M36x3	125	60	166	15	40	55	48	58	0.6	6	140	146	1.5		
SI40ET-2RS	40	28	53	24	92	M39x3	142	65	188	18	47	60	52	65	0.6	7	175	180	2.1		
SI45ET-2RS	45	32	60	28	102	M42x3	145	65	196	20	52	65	58	70	0.6	7	225	240	2.7		
SI50ET-2RS	50	35	66	31	112	M45x3	160	68	216	20	57	70	62	75	0.6	6	275	290	3.5		
SI60ET-2RS	60	44	80	39	135	M52x3	175	70	242.5	20	68.5	80	70	88	1	6	430	450	5.6		
SI70ET-2RS	70	49	92	43	160	M56x4	200	80	280	20	81	85	80	98	1	6	550	610	8.3		
SI80ET-2RS	80	55	105	48	180	M64x4	230	85	320	25	91	95	95	110	1	6	705	750	13		